
- 3. (Amended) An anticorrosive lubricant composition for molded plastic products according to claim 1, wherein said poly  $\alpha$ -olefin is a mixture of one kind or not less than two kinds, selected from the group of oligomers of decene-1 such as a dimer, trimer, tetramer, and so forth, of decene-1.
- 4. (Amended) An anticorrosive lubricant composition for molded plastic products according to claim 1, wherein said corrosion prevention additive is a sulfonate based anticorrosive.
- 5. (Amended) An anticorrosive lubricant composition for molded plastic products according to claim 1, wherein said sulfonate based anticorrosive is one kind or not less than two kinds, selected from the group consisting of Li-sulfonate, Ba-sulfonate, Casulfonate, and Zn-sulfonate.
- 6. (Amended) Molded plastic products to which said anticorrosive lubricant composition for molded plastic products according to claim 1 is applied, and which is composed of one kind of resin, or not less than two kinds of resins, selected from the group consisting of polycarbonate resins, ABS resins, polystyrene resins, and polycarbonate-ABS resins.



- 3. (Amended) An anticorrosive lubricant composition for molded plastic products according to claim 1 or claim 2, wherein said poly  $\alpha$ -olefin is a mixture of one kind or not less than two kinds, selected from the group of oligomers of decene-1 such as a dimer, trimer, tetramer, and so forth, of decene-1.
- 4. (Amended) An anticorrosive lubricant composition for molded plastic products according to any ene of claims 1 to 3 claim 1, wherein said corrosion prevention additive is a sulfonate based anticorrosive.
- (Amended) An anticorrosive lubricant 5. composition for molded plastic products according to any one of claims 1 to 4 claim 1, wherein said sulfonate based anticorrosive is one kind or not less than two kinds, selected from the group consisting of Li-sulfonate, Ba-sulfonate, Ca-sulfonate, and Zn-sulfonate.
- 6. (Amended) Molded plastic products to which said anticorrosive lubricant composition for molded plastic products according to any one of claims 1 to 5claim 1 is applied, and which is composed of one kind of resin, or not less than two kinds of resins, selected from the group consisting of polycarbonate resins, ABS resins, polystyrene resins, and polycarbonate-ABS resins.